

Material Safety Data Sheet

ULTRAVIS

Product Identification

MANUFACTURER'S NAME Control Chemical (1989) Corporation
MANUFACTURER'S ADDRESS..... 7016 - 30 Street S.E.
Calgary, Alberta, Canada T2E
EMERGENCY PHONE NUMBER..... (403) 720-7044
SUPPLIER IDENTIFIER.....
SUPPLIER'S ADDRESS.....
SUPPLIER'S EMERGENCY PHONE NUMBER.....
PRODUCT IDENTIFIER..... ULTRAVIS
PRODUCT USE..... DRILLING MUD

Hazardous Ingredients of Materials

Chemical Identity	Concentration	CAS#/NA#/UN#	LD(50)	LC(50)
Mineral Spirits	20-40%	CAS 64742-47-8	N/E	N/E
Alkyl Phenol Ethoxylate	3-7%	CAS 68412-54-4	(Oral, Rat) 3,000 mg/kg (Dermal, Rabbit) 2,830 mg/kg	
Ethoxylated C12-15 Alcohol	<1.6%	CAS 68131-39-5	(Oral, Rat) 2,500 mg/kg	

Physical Data For Product

PHYSICAL STATE..... Liquid
ODOUR AND APPEARANCE Oily smell, liquid emulsion
ODOUR THRESHOLD..... N/E
SPECIFIC GRAVITY 0.98
VAPOUR PRESSURE N/E
VAPOUR DENSITY (air=1)..... N/E
EVAPORATION RATE..... N/E
BOILING POINT N/E
FREEZING POINT N/E
pH 7.0 - 9.0 (0.6% in distilled water)
DENSITY (g/ml) N/E
COEFFICIENT OF WATER/OIL DISTRIBUTION N/E

Fire and Explosion Hazard of Product

CONDITIONS OF FLAMMABILITY requires source of ignition, presense of air and temperature greater than flashpoint
MEANS OF EXTINCTION In case of fire use water spray, foam, dry chemical, or CO2 AVOID USE OF
WATER-SLIPPERY CONDITIONS WILL OCCUR.
FLASHPOINT AND METHOD OF DETERMINATION . 70 c. (C.C.)
UPPER EXPLOSION LIMIT(% BY VOL) N/E
LOWER EXPLOSION LIMIT(% BY VOL) N/E
AUTO-IGNITION TEMPERATURE N/E
FLAMMABILITY CLASSIFICATION..... Combustible Liquid Class B-3
HAZARDOUS COMBUSTION PRODUCTS..... Oxides of carbon or nitrogen and products of incomplete combustion.
EXPLOSION DATA N/E
SENSITIVITY TO STATIC DISCHARGE Potential for fire and/or explosion when used indoors.

Material Safety Data Sheet

ULTRAVIS

Reactivity Data

CHEMICAL STABILITY	Stable
INCOMPATIBLE MATERIALS	Avoid strong oxidizing and reducing materials.
CONDITIONS OF REACTIVITY	Avoid contamination with reactive materials.
HAZARDOUS DECOMPOSITION PRODUCTS	N/E

Toxicological Properties of Product

ROUTES OF ENTRY	
SKIN CONTACT	May cause irritation, redness, swelling or dermatitis.
SKIN ABSORPTION	N/A
EYE.....	Will cause painful burning or stinging of eyes and lids, watering of eyes and inflammation.
INHALATION.....	N/A
INGESTION	May cause nausea or vomiting.
ACUTE OVER EXPOSURE EFFECTS	N/E
CHRONIC OVER EXPOSURE EFFECTS	Skin irritation or dermatitis may occur upon frequent or prolonged contact.
EXPOSURE LIMITS.....	Contains traces of acrylamide, TWA _{EV} =0.03 mg/mg ₃ (ONT.>REG 654/86)
IRRITANCY OF PRODUCT	Skin-moderate eye-moderate
SENSITIZATION TO MATERIAL.....	Repeated or prolonged exposure may cause sensitization in some individuals.
CARCINOGENICITY, REPRODUCTIVE EFFECTS	N/E
TERATOGENICITY, MUTAGENICITY	N/E
TOXICOLOGICALLY SYNERGISTIC PRODUCTS	N/E

Preventive Measures

PERSONAL PROTECTIVE EQUIPMENT	Wear eye/face protection. Wear suitable gloves.
SPECIFIC ENGINEERING CONTROLS	General ventilation with a good source of make-up air recommended for all indoor situations.
LEAK AND SPILL PROCEDURES.....	Contain the spill, soak up with an absorbent material. Clean with an adequate solvent.
WASTE DISPOSAL.....	In accordance with Municipal, Provincial and Federal regulations.
HANDLING PROCEDURES AND EQUIPMENT	N/A
STORAGE REQUIREMENTS	Store in a tightly sealed container.
SPECIAL SHIPPING INFORMATION	Not Regulated.

First Aid Measures

SPECIFIC FIRST AID PROCEDURES.....	FLUSH EYES WITH WATER. RINSE CONTAMINATED SKIN WITH SOAP AND WATER. IF INGESTED, GIVE WATER. DO NOT INDUCE VOMITING. CALL A PHYSICIAN. IN CASE OF DISCOMFORT BY VAPORS OR DUSTS, MOVE TO A VENTILATED AREA.
------------------------------------	---

Preparation Date of Material Safety Data Sheet

PREPARED BY.....	Control Chemical (1989) Corporation
PHONE NUMBER OF PREPARER.....	(403) 720-7044
DATE PREPARED	January 2, 2010

The information contained herein is based on data believed to be reliable, but is presented without guarantee or warranty and Control Chemical (1989) Corporation disclaims any liability incurred from the use thereof.