



Distributed by: America West Drilling Supply
800-800-8444 | 775-355-1199



30 NV

- Oilfield tough
- Pressure seal lip type packing
- Ball bearing upthrust
- Main bearing – Full Apex roller
- Oil lubrication – 7 gallons
- Two (2) needle roller bearings for maximum shaft alignment
- Saver sub to 6 5/8 Reg LH pin
- Shank adapter available

TECHNICAL

LENGTH	WIDTH	WEIGHT	HOSE CONN.	LOWER CONN.	FLUID PASSAGE	WORKING PRESSURE
93"	33"	3960	4" LP 8- rd	5 1/2" REG LH BOX	3"	TO 4500 PSI

WEIGHT CAPACITY

STATIC	ROTATING
300 TONS	193 TONS @ 100 RPM (API)

PARTS LIST

PART NUMBER	NAME	QTY. REQ.	
30NV-6720-XX	SWIVEL, BAIL, 4" LINE PIPE HOSE CONNECTION 2" NPT FEMALE WIRELINE PASSAGE, 5 1/2" REG LH BOX STEM CONNECTION WITH 6 5/8" REG LH PIN SAVER SUB		

Other sizes of connections available, please consult factory.

Option for above swivel, may affect pricing of complete swivel. Other options available, please consult factory.

