



Distributed by: America West Drilling Supply
800-800-8444 | 775-355-1199

4.5PE Side Inlet Swivel



- Fluid Passage
- Replaceable Wearsleeves
- Superior Shaft Alignment
- Sealed Bearing Cases
- Working Pressures to 1500 PSI with optional packing.
- Simple Bolt Together Design

TECHNICAL DATA

LENGTH	WIDTH	WEIGHT	HOSE CONN.	UPPER CONN.	LOWER CONN.	WATERCOURSE	WORKING PRESSURE
19 ¼ Shoulder	9	215	2 ½	3 ½ Reg Box	3 ½ IF Pin	2 ½	To 1500 PSI

PARTS LIST

PART NUMBER	NAME	NUMBER REQ.	
4.5PE-4700-XX	SIDE INLET SWIVEL, 3 ½" REG. RH BOX UPPER CONNECTION, 2 ½" NPT FEMALE HOSE CONNECTION, WITH 3 ½" IF RH PIN LOWER CONNECTION		
	ADD FOR SPECIAL STEM OR 4 1/8" DI-31 RH BOX		
4.5PE-01A**	STEM, 3 ½" REG RH BOX BY 3 ½" IF RH PIN	1	
4.5PE-01F**	STEM, 3 ½" IF RH BOX BY 4 1/8" DI-31 RH BOX	OPTION	
4.5PE-02	OUTER SEAL	2	
4.5PE-03	BEARING	2	
4.5PE-04A	PACKOFF BOX, 2 ½" NPT FEMALE HOSE CONNECTION	OPTION	
4.5PE-06	TOP GLAND	2	
4.5PE-07	INNER HOUSING SEAL	2	
4.5PE-08	WEAR SLEEVE	2	
4.5PE-09	BEARING HOUSING	2	
4.5SIW-05	PACKING SET	2	
4.5SIW-05-LOW	PACKING SET (10 TO 125 PSI)	OPTION	
4.5SIW-05-417	PACKING SET, HIGH PRESURE	OPTION	
4.5SIW-05A	LANTERN RING	2	
OR-261	O-RING (TOP GLAND)	2	

Other sizes of connections available, please consult factory.

Option for above swivel, may affect pricing of complete swivel. Other options available, please consult factory.

